

## 20.H43 SERIES TYRE INFLATOR



The 20.H43 Tyre Inflator features a lightweight, ergonomic design. Its tough, die-cast aluminium body encased in an ABS shell with an impact absorbing bumper is designed to last. It has a large 80 mm multi scale dial gauge for ease of reading. Easy to operate, using the trigger to inflate and deflate.

### FEATURES

- » 1/4" female inlet
- » Large 80mm Analogue dial display
- » Range: 174 Psi (12 Bar)
- » Accuracy: complies with BSEN 12645:2014
- » Scale: Psi and Bar
- » Inflate, deflate and Tyre pressure
- » Max supply pressure: 200 Psi
- » Inflation volume: 1200 L/Min @ 200 Psi
- » Wire sheathed rubber hose, nylon braided
- » Rated IP 44
- » User manual, calibration certificate included
- » Dimensions (LxWxH): 235 x 90 x 110 mm
- » 1 Year Warranty



CE EN 12645:2014

| MODEL   | HOSE LENGTH | CONNECTOR      | WEIGHT | PACKAGE SIZE (CM) | QTY PER BOX | BOX SIZE (CM) |
|---------|-------------|----------------|--------|-------------------|-------------|---------------|
| H.43.02 | 1.8 MTR     | SINGLE CLIP ON | 1 KG   | 37x18x8           | 20          | 78x37x37      |

Contact: Pete Littlewood

T +44 (0) 1909 768468 - M +44 (0) 7583 313909

E sales@jpiequipment.co.uk - www.jpiequipment.co.uk