

20.W90 AUTOMATIC TYRE INFLATOR



The 20.W90 automatic digital tyre inflator represents quality and digital accuracy at an economical price. The classic design, with 9 m hose, allows the operator to preset the required pressure and move to a safe distance whilst the tyre is inflated. Suitable for a multitude of applications and environments.

Designed to meet EC standards and featuring a sturdy, lightweight ABS casing, the large LCD display is easy to read. Use the two preset buttons to store your "favourite" pressure. The over pressure setting (OPS) option allows automatic beadseating and deflation back to the required tyre pressure.

FEATURES

- » 1/4" female inlet
- » LCD digital display
- » ABS housing
- » Scale: Psi, Bar or kPa
- » Range: 174 Psi (12 Bar)
- » Max supply pressure: 182 Psi
- » Accuracy: complies with BSEN 12645:2014
- » Inflation volume: 3000 L/Min @ 182 Psi
- » Auto inflate, Auto deflate, Over Pressure Setting
- » Diagnostics, Error reporting, Audible warnings
- » Power supply: 240V AC (50-60Hz)
- » Dimensions (LxWxH): 230x278x85 mm
- » User manual, calibration certificate included
- » 1 Year Warranty



CE EN 12645:2014

MODEL	HOSE LENGTH	PLUG	CONNECTOR	WEIGHT	PACKAGE SIZE (CM)	QTY PER BOX	BOX SIZE (CM)
20.W90.UK	10 MTR	UK (3 PIN)	SINGLE CLIP ON	5.5 KG	28x21x16	6	37x30x36
20.W90.EU	10 MTR	EU (2 PIN)	SINGLE CLIP ON	5.5 KG	28x21x16	6	67x30x36

Contact: Pete Littlewood

T +44 (0) 1909 768468 - M +44 (0) 7583 313909

E sales@jpiequipment.co.uk - www.jpiequipment.co.uk