

TDR3000 DIGITAL TYRE INFLATOR

PART NO. 10.30120S

The TDR3000 Digital has the same tough aluminium housing as the original but has been redesigned to make it more compact with a larger LCD display. It has dual shock bumpers, coil spring hose protection, dual hold on chuck, with a backlit digital display, inflates up to 174 psi with an accurate multi-scale gauge which has auto ON and auto OFF.

- Includes certificate of calibration
- Accuracy exceeds EC Standards
- Multi-scale gauge
- Serial / batch numbered
- Backlit display
- Wire sheathed hose eliminates kinking
- Impact absorbing bumpers
- Rubber grip on chuck
- Tough die cast aluminium body
- Packaged in colour display box
- Includes:
 - Inflator
 - Hose
 - Instruction manual with calibration certificate



SPECIFICATIONS	
Reader unit	Digital with backlit display
Chuck type	Hold on
Chuck style	Dual angle
Inlet size	1/4"
Hose length	500 mm
Dimensions	200L x 40W x 80H mm + hose + chuck
Weight	0.85 kg
Accuracy	± 2 psi @ 25 - 75 psi
Operation	Inflate, deflate, measure
Supply pressure max.	200 psi
Scale / Max. inflation	174 psi, 1200 kPa, 12 bar
Powered by	2 x AAA Batteries (included)
Battery life (continuous use)	80 hr
Inflation volume litres p/m	500 L/min @ 188 psi
IP rating	No
Notes	Auto ON once pressure is sensed or air inflation takes place/ Auto OFF (8 seconds)
Advised application	Industrial, workshops
Barcode	9312652092823



SCAN QR CODE TO WATCH THE TDR3000 VIDEO

CE COMPLIES WITH EN12645: 2014*

WARNING: Air pre-filters must be used with this inflator to ensure product accuracy and longevity.

*Tyre pressure measuring instruments. Devices for inspection of pressure and/or inflation/deflation of tyres for motor vehicles.

VARIANTS		
Part No.	10.30120S2	10.30120S3
Chuck type	Clip on	Clip on
Chuck style	Dual angle	Single straight
Hose length	2700 mm	1800 mm